

2005年10月6日 14時29分

NO. 2943 P. 9

(10)



JAPANESE PATENT OFFICE

PATENT ABSTRACTS OF JAPAN

(11) Publication number: 10109018 A

(43) Date of publication of application: 28.04.98

(51) Int. Cl.
 B01D 53/04
 B01D 53/30
 B01D 53/56
 B01D 53/86

(21) Application number: 0834488

(22) Date of filing: 04.10.98

(71) Applicant: BABCOCK HITACHI KK

(72) Inventor:
 MORI YOSHIMICHI
 ISHIKAWA TOMIHISA
 NAGAI YOSHINORI

(54) WASTE GAS DENITRATION METHOD AND
 DEVICE THEREFOR

denitration catalyst is evaluated by these denitration rate.

(57) Abstract:

PROBLEM TO BE SOLVED: To provide a method capable of confirming a denitration performance based on an usual operation data and to provide a waste gas denitration method and device capable of forecasting a catalyst replacing or increasing time by executing a forecast of a catalyst life.

SOLUTION: At the time of purifying the waste gas with a denitration catalyst in the presence of the reducing agent, a denitration rate at NOx/NH_3 molar ratio in the waste gas at an evaluation condition, the denitration rate at waste gas amount at the evaluation condition, the denitration rate at waste gas temp. at the evaluation condition or the denitration rate at the NOx concn. at a denitration device inlet are required respectively by using a waste gas amount, waste gas temp., NOx concn. at a denitration device inlet, NOx concn. at a denitration device outlet, NH_3 amount to be injected to the denitration device and NH_3 amount at the denitration device outlet as a data concerning the denitration performance, and a degradation degree of the

COPYRIGHT: (C)1998, JPO



BEST AVAILABLE COPY

Disclaimer:

This English translation is produced by machine translation and may contain errors. The IPC, the INPI, and those who drafted this document in the original language are not responsible for the result of the translation.

Notes:

1. Untranslatable words are replaced with asterisks (***).
2. Texts in the figures are not translated and shown as it is.

Translated: 05:07:49 IST 12/18/2008

Dictionary: Last updated 12/10/2008 / Priority:

[Document Name] Description

[Title of the Invention] The exhaust gas denitrogenization method and equipment

[Claim(s)]

[Claim 1] The exhaust gas denitrogenization method characterized by recording the data about denitrogenization performance, converting into predetermined evaluation conditions in the exhaust gas denitrogenization method which purifies exhaust gas according to a NO_x removal catalyst under existence of a reducing agent, evaluating denitrogenization performance, and evaluating the degree of degradation of a NO_x removal catalyst.

[Claim 2] As data about denitrogenization performance, the amount of exhaust gas, exhaust gas temperature, NO_x removal equipment entrance NO_x concentration, NO_x removal equipment exit NO_x concentration, pouring NH₃ quantity to NO_x removal equipment, and NO_x removal equipment exit NH₃ quantity are used. The NO_x removal efficiency in the molar ratio of the ammonia in exhaust gas to NO_x in exhaust gas at the time of evaluation conditions, The exhaust gas denitrogenization method according to claim 1 which searches for the NO_x removal efficiency in the amount of exhaust gas at the time of evaluation conditions, the NO_x removal efficiency in the exhaust gas temperature at the time of evaluation conditions, or the NO_x removal efficiency in the NO_x removal equipment entrance NO_x concentration at the time of evaluation conditions, and is characterized by evaluating the degree of degradation of a NO_x removal catalyst according to such NO_x removal efficiency.

[Claim 3] The amount of exhaust gas is the exhaust gas denitrogenization method according to claim 1 or 2 characterized by asking with the function which measures the amount of direct flue gas, or calculates an amount of combustion gas from the air content for combustion.

[Claim 4] The exhaust gas denitrogenization method according to claim 1 to 3 characterized by using for exhaust gas processing from an incinerator.

[Claim 5] The amount of exhaust gas is the exhaust gas denitrogenization method according to claim 4 characterized by asking with a predetermined function from the amount of refuse disposal, the calorific value of garbage, and incinerator exit oxygen concentration.

[Claim 6] It is the exhaust gas denitrogenization method according to claim 5 characterized by calculating the calorific value of garbage by a predetermined function from incinerator exit oxygen concentration.

[Claim 7] In the exhaust gas NO_x removal equipment by the catalytic reduction method which purifies exhaust gas according to a NO_x removal catalyst under existence of a reducing agent Each detection means of the amount of exhaust gas, exhaust gas temperature, NO_x removal equipment entrance NO_x concentration, NO_x removal equipment exit NO_x concentration, pouring NH₃ quantity to NO_x removal equipment, and NO_x removal equipment exit NH₃ quantity, The NO_x-removal-efficiency calculation means in the molar ratio of the ammonia in exhaust gas [as opposed to NO_x in exhaust gas at the time of evaluation conditions based on the detection value of each of said detection means], Exhaust gas NO_x removal equipment characterized by establishing the NO_x-removal-efficiency calculation means in the NO_x removal equipment entrance NO_x concentration at the time of the NO_x removal efficiency in the NO_x-removal-efficiency calculation means in the amount of exhaust gas at the time of evaluation conditions, and the exhaust gas temperature at the time of evaluation conditions, or evaluation conditions.

[Claim 8] Exhaust gas NO_x removal equipment according to claim 7 characterized by using for exhaust gas processing from an incinerator.

[Detailed Description of the Invention]

[0001]

[Field of the Invention] Especially this invention relates to the exhaust gas denitrogenization method and equipment with easy performance management of the NO_x removal catalyst which was suitable for the catalyst NO_x removal equipment of refuse incineration equipment about the exhaust gas denitrogenization method and equipment.

[0002]

[Description of the Prior Art] The flue-gas-denitrogenization method by the alternative contact reduction which used ammonia (NH₃) as the reducing agent is broadly used as a method of removing the nitrogen oxide (NO_x) in the exhaust gas discharged from a thermal power plant, various factories, etc. Said exhaust gas is operated where the quantity, quality, etc. are stabilized mostly, and evaluation management of denitrogenization performance is performed comparatively easily by everyday operation management.

[0003] Since it combines with the increase in such a plant being expected further from now on from many situations, such as an increase in population, and reduction of a reclamation lot, about a municipal-solid-waste incineration system and is installed in the urban-areas suburbs on the other hand, Sufficient smoke-eliminating processing is required and it is necessary to attach exhaust gas denitrizer to a municipal-solid-waste incineration system.

[0004] In a municipal-solid-waste incineration system, the quality of the garbage to process differs, and since the amount of garbage injections to an incinerator is not constant, either, the amount of exhaust gas is uncontrollable with a season, the weather, and a time zone. Thus, since gas conditions are sharply changed with the quality of garbage, the amount of injections, etc., from the usual performance data, it is difficult also for the performance of catalyst NO_x removal equipment to perform the right evaluation.

[0005] [this] in order to grasp denitrogenization performance By making into a sample the catalyst of the specification general and usually same as the catalyst with which it was filled up, the method of evaluating by carrying out direct measurement of a catalyst's own degradation state inserted from the side of the NO_x removal reactor etc., extracted it periodically, and after measuring performance, it was carrying out conversion evaluation at system plan conditions. and a basis [evaluation result / this] -- exchange of a catalyst - - stacking -- increase -- time -- it had measured. For this reason, the number of times of the catalyst quality assessment increased, and catalyst degradation was not able to be evaluated promptly, such as performing this in the pitch of a years time.

[0006] Moreover, there were also many cases which a big difference produces in said sample catalyst and a system catalyst, and the method in particular of catalyst life management of the NO_x removal equipment for refuse incineration equipment was not

what was established.

[0007]

[Problem to be solved by the invention] Exhaust gas conditions do not fix refuse incineration equipment with quality, the amount of injections, etc. of garbage. Since gas volume, entrance NO_x concentration, etc. changed continuously when the performance of NO_x removal equipment is managed only with the performance data (Exit NO_x, the NH₃ amount used, etc.) about the usual denitrogenization managed, there was a problem that the quality assessment in the same conditions was not made and grasp of exact denitrogenization performance could not be performed. The technical problem of this invention loses the fault of the above-mentioned conventional technology, is offering the method of denitrogenization performance making it possible based on the usual performance data, performs catalyst life prediction, and there is in offering the exhaust gas denitrogenization method and equipment which can predict catalyst exchange or product increase time.

[0008]

[Means for solving problem] The technical problem of above-mentioned this invention is solved by the next composition. That is, in the exhaust gas denitrogenization method which purifies exhaust gas according to a NO_x removal catalyst under existence of a reducing agent, it is the exhaust gas denitrogenization method of recording the data about denitrogenization performance, converting into predetermined evaluation conditions, evaluating denitrogenization performance, and evaluating the degree of degradation of a NO_x removal catalyst.

[0009] As data about said denitrogenization performance, for example, the amount of exhaust gas, exhaust gas temperature, NO_x removal equipment entrance NO_x concentration, NO_x removal equipment exit NO_x concentration, pouring NH₃ quantity to NO_x removal equipment, Using NO_x removal equipment exit NH₃ quantity, the NO_x removal efficiency in the NH₃/NO_x molar ratio in exhaust gas at the time of evaluation conditions, The NO_x removal efficiency in the amount of exhaust gas at the time of evaluation conditions, the NO_x removal efficiency in the exhaust gas temperature at the time of evaluation conditions, or the NO_x removal efficiency in the NO_x removal equipment entrance NO_x concentration at the time of evaluation conditions is searched for, and such NO_x removal efficiency estimates the degree of degradation of a NO_x removal catalyst.

[0010] Here, the amount of exhaust gas can be calculated with the function which

measures the amount of direct flue gas, or calculates an amount of combustion gas from the air content for combustion.

[0011] The technical problem of above-mentioned this invention is solved by the next composition. Namely, it sets to the exhaust gas NO_x removal equipment by the catalytic reduction method which purifies exhaust gas according to a NO_x removal catalyst under existence of a reducing agent. Each detection means of the amount of exhaust gas, exhaust gas temperature, NO_x removal equipment entrance NO_x concentration, NO_x removal equipment exit NO_x concentration, pouring NH₃ quantity to NO_x removal equipment, and NO_x removal equipment exit NH₃ quantity, Based on the detection value of each of said detection means, the NO_x-removal-efficiency calculation means in the NH₃/NO_x molar ratio at the time of evaluation conditions, It is the exhaust gas NO_x removal equipment which established the NO_x-removal-efficiency calculation means in the amount of exhaust gas at the time of evaluation conditions, the NO_x-removal-efficiency calculation means in the exhaust gas temperature at the time of evaluation conditions, or the NO_x-removal-efficiency calculation means in the NO_x removal equipment entrance NO_x concentration at the time of evaluation conditions.

[0012] Moreover, this invention can be used for exhaust gas processing from an incinerator, and can calculate the amount of exhaust gas in that case with a predetermined function from the amount of refuse disposal, the calorific value of garbage, and incinerator exit oxygen concentration. Moreover, the calorific value of garbage can also be calculated with a predetermined function from incinerator exit oxygen concentration. As the above-mentioned refuse incineration equipment, equipment of a stalker method, a fluid bed method, a kiln method, or a machine batch method is used.

[0013]

[Function] Denitrogenization performance is mainly influenced by the amount of exhaust gas, NO_x removal equipment entrance NO_x concentration, gas temperature, and the NH₃/NO_x molar ratio (NH₃ injection rate). Then, the denitrogenization performance in an actual measurement is converted to plan conditions by making the relation of each influence factor and denitrogenization performance into a function using the function of the relation between an influence factor and NO_x removal efficiency about each influence factor. For example, the survey amount of exhaust gas and survey NO_x removal efficiency are inputted to the variable in a function, and this asks for the denitrogenization performance in plan conditions. In this way, even if it is the case where exhaust gas conditions change with change of garbage quality etc. continuously, for example, the performance comparison by the basis of certain conditions is always possible, and grasp of degradation etc. can be performed easily.

[0014]

[Mode for carrying out the invention] The form of operation of this invention is explained below. Refuse incineration equipment of one work example of this invention is shown in drawing 1. Although the composition of the apparatus which constitutes it according to the scale of refuse incineration equipment differs somewhat, the refuse incineration equipment shown in drawing 1 is common.

[0015] The exhaust gas discharged from the incinerator 1 passes along a condenser 2, the alkali spray tower 3, and the bag filter 4. NH_3 used as a reducing agent are poured into the flue 7 by the side of the style before NO_x removal reactor 5, NO_x in exhaust gas is removed by operation of the NO_x removal catalyst with which it filled up in NO_x removal reactor 5, and the purified exhaust gas is discharged from a chimney 6. Air is supplied to the incinerator 1 from an air fan, and garbage is thrown in from an entrance slot 16. In addition, the air for combustion is introduced into the incinerator 1 from the air fan 15 having the airometer 13.

[0016] To the flue 7 of the style before NO_x removal reactor 5, Entrance NO_x , O_2 analysis 8 [a total of] (it samples from one measurement seat and measures with a NO_x analysis meter and O_2 analysis plan, respectively.), The exhaust gas flow instrument 11 and the exhaust gas thermometer 14 are arranged, and Exit NO_x , O_2 analysis 9 [a total of], and exit NH_3 analysis 10 [a total of] are ****-it-arranged at the flue 7 of NO_x removal reactor 5 slipstream, and NH_3 injection rate is measured with NH_3 flow instrument 12.

[0017] As the data about the performance of NO_x removal equipment is recorded and the control block diagram of this example is shown in drawing 2 in such a system, a computer with the function converted into certain evaluation conditions is formed, and it carries out as [be / evaluation of equipment performance / possible] if needed. The procedure is explained hereafter.

[0018] (1) The amount of exhaust gas according to the exhaust gas flow instrument 11 in the flue 7 of bag filter 4 slipstream as the above-mentioned evaluation factor, Entrance NO_x , the entrance NO_x concentration measured by O_2 analysis 8 [a total of], Exit NO_x , The molar ratio of NO_x in exhaust gas to pouring NH_3 to NO_x removal reactor 5 for which it asked from the exit NO_x concentration measured by O_2 analysis 9 [a total of] and exit NH_3 concentration measured by exit NH_3 analysis 10 [a total of] (-- it may be hereafter called a pouring molar ratio) -- [it uses, and a denitrogenization quality assessment value is calculated with the function about each influence factor, and] It converts to certain evaluation conditions (if a molar ratio is calculated from NH_3 poured-in quantity, theory is not suited in many cases, and a molar ratio with more exact asking

from exit NH₃ concentration, Entrance NO_x, and NO_x removal efficiency is obtained.). For this reason, when there is exit NH₃ analysis 10 [a total of], a molar ratio is computed from exit NH₃ concentration. .

[0019] (2) When not installing exit NH₃ analysis 10 [a total of] among the evaluation factors of the above (1), from NH₃ flux measured with the flow instrument 12 which detects the flux of NH₃ which are a reducing agent, ask for a pouring molar ratio and convert with each influence factor.

[0020] (3) Among the evaluation factors of the above (1), the amount of exhaust gas incorporates and calculates the function (the gas volume characteristic in real gas is arranged and function-ized by a relation with an air content.) which calculates an amount of combustion gas from the air content measured with air content 13 [a total of] for refuse incineration, and converts it with each influence factor.

[0021] In order to calculate the amount of exhaust gas among the evaluation factors of the above (1), garbage quality according to a season (4) Low quality, The function (the gas volume characteristic in real gas is arranged and function-ized by a relation with a season.) which calculates respectively the amount of exhaust gas which makes a function the season in the time of using and evaluating O₂ analysis a total of eight measured value of an incinerator exit to the calorific value of the garbage corresponding to this garbage quality since it usually reaches and is classified into the nature garbage of high is incorporated. It converts with each influence factor.

[0022] Each influence factor which was measured as mentioned above or was called for is taken in in computers, such as a central operation room of a plant, and is converted to fixed evaluation conditions by the method described below for every influence factor.

[0023] In addition, the denitrogenization performance at the time of operation is usually called for by the following formula from Entrance NO_x, the entrance NO_x concentration measured by O₂ analysis 8 [a total of], and Exit NO_x and the exit NO_x concentration measured by O₂ analysis 9 [a total of]. NO_x-removal-efficiency $\eta_1 = \{(\text{entrance NO}_x - \text{exit NO}_x) / \text{entrance NO}_x\} \times 100 (\%)$

[0024] (1) There is a relation as indicated to be the pouring molar ratio calculated from pouring molar ratio exit NH₃ concentration or NH₃ poured-in quantity and NO_x removal efficiency to drawing 4. Along with a curve, NO_x removal efficiency η_2 at the time of molar ratio (molar ratio to NO_x in exhaust gas of NH₃ in exhaust gas) MD in evaluation conditions (a plan molar ratio or the molar ratio when usually evaluating performance in

each plant is called evaluation conditions.) can be found in NOx removal efficiency η_1 and the pouring molar ratio M_m for which it asked by the upper formula.

[0025] (2) Although it has a relation as shown in drawing 5 between the amount-of-exhaust-gas amount of exhaust gas and NOx removal efficiency and the intersection of NOx removal efficiency η_2 searched for above (1) has the system amount of exhaust gas V_m on the curve shown in drawing 5, if it moves along with this curve, NOx removal efficiency η_3 in the amount of exhaust gas V_D in evaluation conditions can be found.

[0026] (3) The relation between gas temperature exhaust gas temperature and NOx removal efficiency has a relation as shown in drawing 6, the measurement gas temperature T_m and NOx removal efficiency η_3 searched for by the above (2) are moved to the time of the exhaust gas temperature T_D in evaluation conditions along with a curve, and NOx removal efficiency η_4 can be found.

[0027] (4) The relation between entrance NOx concentration NOx concentration and NOx removal efficiency has a relation as shown in drawing 7, the measurement entrance NOx concentration N_m and NOx removal efficiency η_4 searched for by the above (3) are moved to the entrance NOx concentration N_D in evaluation conditions along with a curve, and NOx removal efficiency η_5 can be found.

[0028] It becomes the value which acquired the NOx removal efficiency (measured NOx removal efficiency) in each influence factor which this NOx removal efficiency η_5 measured by having converted it into certain evaluation conditions, and management of the denitrogenization performance in the basis of the same conditions is always attained. The degradation state of denitrogenization performance can manage daily by this, and improvement in reliability of NOx removal equipment can be aimed at.

[0029]

[Effect of the Invention] According to this invention, from the singularity of refuse incineration equipment, it comes to be able to perform a denitrogenization quality assessment with difficult evaluation from everyday performance data, and management, and improvement in reliability is achieved.

[Brief Description of the Drawings]

[Drawing 1] It is the figure showing the system of refuse incineration equipment of one

work example of this invention.

[Drawing 2] It is the control block diagram of the exhaust gas NO_x removal equipment of one work example of this invention.

[Drawing 3] It is a flow chart for NO_x-removal-efficiency calculation of the exhaust gas NO_x removal equipment of one work example of this invention.

[Drawing 4] It is the figure showing the NO_x-removal-efficiency conversion curve to the pouring molar ratio of the NO_x removal equipment used for refuse incineration equipment of one work example of this invention.

[Drawing 5] It is the figure showing the NO_x-removal-efficiency conversion curve to the gas volume of the NO_x removal equipment used for refuse incineration equipment of one work example of this invention.

[Drawing 6] It is the figure showing the NO_x-removal-efficiency conversion curve to the gas temperature of the NO_x removal equipment used for refuse incineration equipment of one work example of this invention.

[Drawing 7] It is the figure showing the NO_x-removal-efficiency conversion curve to the NO_x concentration of the NO_x removal equipment used for refuse incineration equipment of one work example of this invention.

[Explanations of letters or numerals] 1 Incinerator 2 Exhaust Gas Condensator 3 Alkali Spray Tower 4 Bug Filter 5 Catalyst NO_x Removal Reactor 6 Chimney 7 Flue 8 Entrance NO_x, O₂ Analysis 9 [a Total of] Exit NO_x, O₂ Analysis Meter 10 Exit NH₃ Analysis 11 [a Total of] Exhaust Gas Flow Instrument 12 NH₃ Flow Instrument 13 Air Content Meter for Incineration 14 Gas Thermometer 15 Air Fan 16 Garbage Entrance Slot

[Translation done.]